

jc714 U.S. PTO
03/31/00

04 - 03 - 00

A

FISH & RICHARDSON P.C.

4350 La Jolla Village Drive
Suite 500
San Diego, California
92122

Frederick P. Fish
1855-1930

March 31, 2000

W.K. Richardson
1859-1951

Telephone
858 678-5070

Facsimile
858 678-5099

Web Site
www.fr.com

Attorney Docket No.: 10559-148001/P7973

Box Patent Application
Assistant Commissioner for Patents
Washington, DC 20231

Presented for filing is a new original patent application of:

Applicant: ULHAS S. WARRIER AND PRAKASH IYER

Title: NETWORK SESSION MANAGEMENT

jc625 U.S. PTO
09/539928
03/31/00



BOSTON
DELAWARE
NEW YORK
SAN DIEGO
SILICON VALLEY
TWIN CITIES
WASHINGTON, DC

Enclosed are the following papers, including those required to receive a filing date under 37 CFR 1.53(b):

	Pages
Specification	8
Claims	5
Abstract	1
Declaration	[Unsigned]
Drawing(s)	4

Enclosures:
— Postcard.

Basic filing fee	\$0
Total claims in excess of 20 times \$18	\$0
Independent claims in excess of 3 times \$78	\$0
Fee for multiple dependent claims	\$0
Total filing fee:	\$0

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EE647185808US

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit March 31, 2000
Peter F. Consoli
Signature

Peter F. Consoli
Typed or Printed Name of Person Signing Certificate

FISH & RICHARDSON P.C.

Assistant Commissioner for Patents
March 31, 2000
Page 2

Under 37 CFR §1.53(d), no filing fee is being paid at this time. Please apply any other required fees, **EXCEPT FOR THE FILING FEE**, to deposit account 06-1050, referencing the attorney document number shown above.


If this application is found to be incomplete, or if a telephone conference would otherwise be helpful, please call the undersigned at (858) 678-5070.

Kindly acknowledge receipt of this application by returning the enclosed postcard.

Please send all correspondence to:

SCOTT C. HARRIS
Fish & Richardson P.C.
4350 La Jolla Village Drive
Suite 500
San Diego, CA 92122

Respectfully submitted,

 Reg. No. 42,945 For
Scott C. Harris
Reg. No. 32,030

Enclosures
SCH/sym
30013891 doc

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: NETWORK SESSION MANAGEMENT
APPLICANT: ULHAS S. WARRIER AND PRAKASH IYER

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EE647185808US

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

March 31, 2000

Date of Deposit

Signature

Peter F. Consoli

Peter F. Consoli

Typed or Printed Name of Person Signing Certificate

NETWORK SESSION MANAGEMENT

This invention relates to network session management.

BACKGROUND

5 A virtual private network (VPN) is a data service that offers transmission characteristics similar to those of private lines using the public Internet. Remote access VPNs can be used for accessing corporate local area networks (LANs) over public networks from small office home offices (SOHO) where employees of the corporations can work from home. The rise of security technologies such as IPSEC, a secure form of the Internet Protocol with optional authentication and encryption, as well as improved quality of service (QoS) has made VPN applications practical. At the same time, the rise in high-speed communication lines such as asymmetric digital subscriber lines (ADSL) and cable modems has increased the vulnerability of the VPNs because they provide conduits for hackers on the public Internet to access sensitive information on a corporate network during a VPN session.

10
15
20 IT administrators can impose restrictions on network access privileges of the remote system to the corporate LAN during a VPN session. For example, during a VPN session between a SOHO and a corporate LAN, the home gateway between the SOHO and the LAN might allow the client access to the printer at home but not to the public Internet. In many
25 situations the home office user may wish to re-configure the network resources based on policies delivered from the LAN. VPN clients are not typically home-networking aware and consequently may limit home network usage during VPN sessions. Personal computer (PC) firewalls are configurable, but are not
30 well integrated with VPN clients and cannot enforce dynamic network stack reconfiguration based on policies.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 illustrates a transaction system.

Fig. 2 illustrates a transaction system with a small home office local area network.

Fig. 3 illustrates an embodiment of a network stack.

Fig. 4 is a flow chart of a method of dynamically reconfiguring a network stack during a VPN session.

DETAILED DESCRIPTION

As shown in Fig. 1, a transaction system 100 allows for transactions between a home office and a corporation. A client station such as a SOHO 105 can use a browser 110 or other network software to initiate a network transaction. The SOHO 105 uses its network software to connect to the Internet 115. The SOHO 105 can connect to Public Web Servers on Internet/Other network 120 or can initiate a VPN session with a corporate LAN 135 through this connection with the Internet 115 and through the corporate Access server 125. The corporate LAN 135 can be, for example, a local network or expanded network of computers in a single location or a national or even international location. When the SOHO 105 initiates the VPN session, it is connected with other computers associated with the corporate LAN 135 (based on policies set for corporate LAN 135. Various devices 140, 145 are connected to the corporate LAN 135 for access from other devices on the LAN or a SOHO/remote device 105.

The corporate Access server 125 can include a policy engine 126 having a list of policies that grant privileges to a variety of users. The policy engine 126 is used to create filters 127 that permit or deny users access to the devices 140, 145 on the corporate LAN 135.

Fig. 2 illustrates the system 100 of Fig. 1 with an expanded view of the SOHO 105 as a network 200. A SOHO LAN 205 can have several attached devices including a PC 210 that initiates a VPN session, a printer 215 and other devices 220.

During a VPN session, the device that initiated the VPN session also can function as a node in the SOHO network 200. For example, in a typical SOHO network 200, the VPN device 210 can perform the role of a gateway. Other devices such as the PC 225 can access services available on the VPN PC 210, or the VPN PC 210 can access printer 215 or other devices 220 on the SOHO network 200.

Sharing the SOHO network 200, however, should not compromise the security of the corporate LAN 135. Other PCs such as the PC 225 should be able to access the corporate LAN 135 through the VPN PC 210. Conversely, other devices 140, 145 on the corporate LAN 135 should not be able to access PCs on the SOHO network 200. If the VPN PC 210 is also the gateway, then other PCs on the SOHO network such as PC 225 should be able to access Public servers or other network 120 without compromising security of the SOHO network 200 or the corporate LAN 135 or any device associated with the VPN session. However, any nodes on the Internet 120, that is, any unauthorized users, should not be able to access any of the services on the VPN PC 210 during the VPN session. Any such access would be a breach of security of the VPN session and must be avoided.

To enhance the security of the system, the VPN PC 210 has a network stack component 210b. The network stack component 210b includes data storage locations typically accessed in a sequential manner, and defines the parameters of the VPN session. To provide the security and access parameters discussed above, the network stack is dynamically reconfigured during the VPN session. Reconfiguration can be statically pre-determined or can be dynamically controlled by policies downloaded by the VPN PC 210 from 126 during the VPN session setup. Policies can be fine-grained or coarse-grained. A fine-grained policy can be, for example, a rule that creates a very narrowly defined filter to control the data flow on a specific network interface. A coarse-grained policy can, for example, be a rule that creates a more broadly defined filter

to control the data flow on a larger class or type of network interface.

Fig. 3 illustrates an embodiment of a network stack 210b that can be reconfigured during a VPN session. The VPN PC 210 can have a number of applications running on it such as applications 305. A policy store 320 serves as a repository for policies from the policy engine 126 that are updated by retrieving policies from the Access server 125 each time a VPN session is initiated. An augmented policy engine 310 is an extension of the policy engine 126 on the Access server 125. The augmented policy engine 310 uses policy rules from the policy store 320 and applies the rules to both application context priorities as well as data traffic over the network. For example, a policy rule may allow a particular word processing application on the VPN PC 210 to access a document located on the device 140 on the corporate LAN 135. The word processing program also has associated with it an application context that determines its priority in accessing the device 140. Furthermore, policy rules may apply to the network data traffic. Network flow is tracked using various factors such as the type of flow (local or remote origination), network interfaces, destination network address, and source (application, user etc.). The augmented policy engine 310 uses the application context along with the network data flow factors to enforce finer-grained packet filtering based on the policy rules in the policy store 320. In this example, the word processing application may be limited not only by the policy rule, but also by its application context and the network data traffic. The finer granularity of control prevents unwanted outsiders from accessing the VPN session. The network stack 210b stores the address space of the LAN 205 to allow the stack 210b to distinguish between devices on the SOHO LAN 205 and devices on the corporate LAN 135, and undesired nodes on the Internet or other network 120. The network stack 210b is thus able to filter packets based on the source and destination.

A socket interceptor 330 serves as a session layer component in the network stack 210b that identifies all active network applications 305. The Portable Operating System Interface UNIX (POSIX) is used to create application sockets and provide a uniform application interface. In one embodiment, the socket interceptor drops packets destined to and from certain applications 305. For example, the socket interceptor drops packets from user logins that are not authorized to be part of a VPN session. In another embodiment, the socket interceptor 330 provides context information for network packets flowing from a packet guard 360 that creates packet filters as they flow into the packet guard. In one embodiment, the socket interceptor can be implemented as a WinSock layered service provider (LSP) on a Microsoft Windows platform. In this way, the socket interceptor 330 acts as an application program interface (API) between Microsoft Windows and TCP/IP protocol software.

In addition to receiving context information from the socket interceptor 330, the packet guard 360 also creates filters from the policies in the policy store 320. The packet guard 360 also can be connected to a predetermined static configuration 365 that also provides filtering criteria. ``Instance'' filtering is dictated by the augmented policy engine 310 based on rules in the policy store 320. In one embodiment, the packet guard layer 360 can be implemented as a Network Driver Interface Specification (NDIS) intermediate driver on the Microsoft Windows platform. In this way the packet guard 360 can offer protocol multiplexing so that multiple protocol stacks can co-exist on the same host.

A Transmission Control/Internet Protocol (TCP/IP) layer that provides the network communication is connected between the socket interceptor 330 and the packet guard 360. A packet translator 350 is connected between the TCP/IP interface 340 and the packet guard layer 360. The packet translator 350 translates data packets to and from the different network locations, in this case, the packets between the corporate LAN 135 and the SOHO LAN 205. In one implementation, the packet

translator can be the Internet standard Network Address Translation (NAT) that allows a company to shield internal addresses from the Internet.

5 A network interface 370 is connected to the packet guard 360. The network interface is the session layer that interfaces the network stack 210b with network software (not shown) to connect the VPN PC 210 to the SOHO LAN 205 and ultimately to the corporate LAN 135.

10 The network stack 210b thus creates an effective ``firewall'' between the VPN session and outside intrusion.

20 To reconfigure the network stack 210b securely and automatically during the VPN session, the network stack 210b senses the VPN session. As shown in Fig. 4, a client begins 405 a VPN session. The network stack 210b receives 410 policies from the Access server 125 and stores 415 the policies in the policy store 320. At this point, the VPN session initially is sensed and the received policies determine what access the client, the SOHO 105 or the SOHO LAN 205, is permitted. The packet guard 360 is used to enforce 420 packet filtering. The packet filtering is performed either by receiving policy rules from the augmented policy engine 310 or by reading the pre-programmed static configuration 365 that determines what packets are filtered. Next, the socket interceptor 330 is created and provides 430 user and/or application context. The socket interceptor 330 can detect and drop 440 packets, for example, from user logins that are not permitted to be part of the VPN session. Packets from any other external PCs (not shown) also are dropped. The socket interceptor 330 also can provide 445 application context information back to the augmented policy engine 320 about applications 305. This context information can be used by the augmented policy engine 310 to further enforce 420 packet filtering. Furthermore, the policies are used to filter 460 packets. Therefore, the network stack 210b is constantly re-configuring itself based on policy rules received from the Access Server 125 and context information provided by the socket interceptor 330 and from the packet

guard, which serves as a ``packet firewall''. The process 400 constantly monitors 450 network configuration changes throughout the VPN session to detect any external intervening and unauthorized processes.

5 Various aspects of the apparatus and methods may be implemented in digital circuitry, or in computer hardware, firmware, software, or in combinations of them. Apparatus can be implemented in a computer products tangibly embodied in a machine-readable storage device for execution by a
10 programmable processor. The foregoing techniques may be performed, for example, by a programmable processor executing a program of instructions to perform functions of the invention by operating on input data and generating output. The methods can be implemented in one or more computer programs that are executable on a programmable system including at least one programmable processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one in/out device, and at least one output device. Each computer program may be implemented in a high-level procedural or object-oriented programming language, or in assembly or machine language. The language may be compiled or interpreted language. Suitable processors include, by way of example, both general and special purpose microprocessors. Generally,
20 a processor will receive instructions and data from read-only memory and/or random access memory. Storage devices suitable for tangibly embodying computer program instructions and data include all forms of non-volatile memory, including by way of example, semiconductor devices, such as EPROM, EEPROM, and
25 flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM disks. Any of the foregoing may be supplemented by or incorporated in, specially designed application-specific integrated circuits (ASICs).

30
35 Possible advantages of the foregoing techniques include dynamic creation of a packet filtering firewall (the packet guard 360), which is driven by policies or static

configurations. Another advantage is the ability to extend policies to include application and/or user context. For example, a corporate policy may temporarily ban the use of a particular browser until patches are applied. Correlating application context and network packet flows can easily enforce such a policy. Another advantage is the ability to confirm continuously that security policies are being applied on the client side.

The foregoing method also can use unified network stack information to enforce the context-based policies. The stack is an aggregation of information across the various layers of the network stack. The combination of application and/or user context to network flow enables the fine-grained control of the network resources in the home office.

Other embodiments are within the scope of the following claims.

What is claimed is:

1 1. A method of managing a network session comprising:

1 delivering policies from a server to a remote system
2 that has predetermined configuration information;

3 establishing a secure connection between the server
4 and the system; and

5 regulating activities in the system based on at
6 least one of the set of policies and the predetermined
7 configuration information.

1 2. The method of claim 1 wherein regulating the activities
2 comprises providing filters that are adapted to reject
3 unauthorized data packets based on rejection criteria.

4 3. The method of claim 2 wherein the rejection criteria
5 include the predetermined static configuration information.

6 4. The method of claim 2 wherein the rejection criteria
7 include the set of policies.

1 5. The method of claim 1 wherein regulating the activities
2 comprises providing a session layer adapted to reject
3 unauthorized data packets based on context such as user and
4 application information.

1 6. The method of claim 1 wherein regulating the activities
2 comprises:

3 providing a session layer adapted to reject unauthorized
4 data packets based on context information; and

5 providing filters adapted to reject unauthorized data
6 packets based on rejection criteria from at least one of the
7 context information and the policies.

1 7. The method of claim 1 further comprising updating the set
2 of policies.

1 8. The method of claim 1 further comprising:
2 detecting data packets from the regulated activities; and
3 rejecting the data packets from the regulated activities.

1 9. An article comprising a computer-readable medium which
2 stores computer-executable instructions for managing a network
3 session, the instructions causing a computer to:

4 receive a set of policies from a server in a remote
5 system having predetermined configuration information;

6 establish a secure connection between the server and the
7 system; and

8 manage activities in the system based on at least one of
9 the set of policies and the predetermined configuration
10 information.

11 10. The article of claim 9, further comprising updating the
12 set of policies.

13 11. The article of claim 9 wherein the instructions to reject
14 the intervening processes comprises instructions to provide
15 filters that are adapted to reject data packets based on
16 rejection criteria.

17 12. The article of claim 11 wherein the rejection criteria
18 includes predetermined static configuration information.

19 13. The article of claim 11 wherein the rejection criteria
20 includes the set of policies.

21 14. The article of claim 9 wherein the instructions to reject
22 the unauthorized activities comprises instructions to provide
23 a session layer adapted to reject unauthorized data packets
24 based on context user and application information.

1 15. The article of claim 9 wherein the instructions to reject
2 the unauthorized activities comprises instructions to:

3 provide a session layer adapted to reject unauthorized
4 data packets based on context information; and

5 provide filters adapted to reject unauthorized data
6 packets based on rejection criteria from at least one of the
7 context information and the policies.

1 16. The article of claim 9, further comprising instructions
2 to:

3 detect unauthorized data packets from the unauthorized
4 activities; and

5 reject the unauthorized data packets from the
6 unauthorized activities.

7 17. A network system, comprising:

8 first and second devices, wherein the first device is
9 adapted to:

10 deliver a set of policies to the second device;

11 and the second device is adapted to:

12 detect data packets from unauthorized activities;
13 and

14 reject the data packets from the unauthorized
15 activities.

1 18. The system of claim 17 further comprising a network
2 stack.

3 19. The system of claim 18, wherein the network stack
4 comprises:

5 a policy engine connected to the first device;

4 a policy store connected to the policy engine;
5 a socket interceptor connected to the policy engine; and
6 a packet guard connected to the policy engine.

1 20. The system of claim 17, the first device further
2 comprising instructions to monitor the system for the
3 intervening processes.

1 21. A network stack, comprising:

2 a policy engine;
3 a policy store adapted to interact with the policy engine
4 and store a set of policies from the policy engine;
5 a socket interceptor coupled to the policy engine;
6 a packet guard coupled to the policy engine.

7 22. The network stack of claim 21 further comprising a packet
8 translator adapted to interact with the socket interceptor and
9 the packet guard.

1 23. The network stack of claim 21 further comprising an
2 interface to a network adapted to connect the network stack to
3 the network, wherein the network has a policy server.

4 24. The network stack of claim 23 further comprising a
5 configurable management process adapted to reconfigure the
6 network stack and having instructions to:

7 receive policies in the policy engine from the policy
8 server;

9 use the socket interceptor to detect and reject data
packets from unauthorized users and applications and provide
the packet guard with context information about the
unauthorized users and applications;

10 use the packet guard to filter unauthorized activities
11 received from the network interface;

12 use the packet guard to filter the data packets from
13 unauthorized users and applications based on the context
14 information received by the socket interceptor; and

15 use the packet guard to filter data packets based on the
16 policies.

Abstract

This invention uses network stack information to enforce context-based policies. The combination of policies, user/application context information and packet filtering is used to enable fine-grained control of network resources.

30004792.doc

- 14 -




Fig. 1

09539928-033100




Fig. 2

09539926-033400

210b




Fig. 3

09539928.033100

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled NETWORK SESSION MANAGEMENT, the specification of which:

[X] is attached hereto.

□ was filed on _____ as Application Serial No. _____ and was amended on _____.

☐ was described and claimed in PCT International Application No. _____ filed on _____
and as amended under PCT Article 19 on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information I know to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Samuel Borodach, Reg. No. 38,388
Stephan J. Filipek, Reg. No. 33,384
George E. Heibel, Reg. No. 42,648
Stuart Macphail, Reg. No. 44,217
Andrew N. Parfomak, Reg. No. 32,431
Frederick H. Rabin, Reg. No. 24,488

Richard P. Ferrara, Reg. No. 30,632
 Scott C. Harris, Reg. No. 32,030
 William J. Hone, Reg. No. 26,739
 Greg O'Bradovich, Reg. No. 42,945
 John B. Pegram, Reg. No. 25,198
 Gary A. Walpert, Reg. No. 26,098

Address all telephone calls to SCOTT C. HARRIS at telephone number (858) 678-5070.

Address all correspondence to SCOTT C. HARRIS at:

FISH & RICHARDSON P.C.
4350 La Jolla Village Drive
Suite 500
San Diego, CA 92122

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patents issued thereon.

[illegible]

Combined Declaration and Power of Attorney

Page 2 of 2 Pages

Full Name of Inventor: ULHAS S. WARRIER

Inventor's Signature: _____ Date: _____

Residence Address: 16840 NW Eastmoreland Ct.
Beaverton, OR 97006

Citizenship: India

Post Office Address: 16840 NW Eastmoreland Ct.
Beaverton, OR 97006

Full Name of Inventor: PRAKASH IYER

Inventor's Signature: _____ Date: _____

Residence Address: 16617 NW Avondale Drive
Beaverton, OR 97006

Citizenship: India

Post Office Address: 16617 NW Avondale Drive
Beaverton, OR 97006

30013888.doc

0013888.doc